



Flammable DOT * Expanded Styrene Adhesive Strong Bonds * Fast Tack

CONTAC FS Foam-Safe Adhesive is a high performance versatile industrial strength contact adhesive designed specifically for adhering extruded / expanded styrene to a variety of substrates. Other applications include wood, plastic, veneers, fiberglass, glass, fabrics, foam, concrete, block, cork drainage mat, expansion joint and particle board. Water resistant and temperature resistant for a variety of applications.



PRODUCT USAGE

For best results, ensure that the adhesives and substrates have been conditioned above 60°F. Make sure that the surfaces are dry and free from dirt, grease, oil or other contaminants. It is always good practice to test specific substrate bonding prior to job. Ensure that the valve on canister is fully open. Position gun 8 to 10 inches away from surface and spray CONTAC FS Foam-Safe Adhesive evenly across the surface without puddling. Spray adhesive on both surfaces to be adhered, horizontally for one and vertically for the other. Allow to dry 2 to 4 minutes until tacky and then join surfaces together applying firm pressure evenly across the bond surface. After use, engage the trigger lock on spray gun and store canister in dry area away from direct sunlight.

STORAGE

Do not store in direct sunlight or in areas with temperatures of 120°F or greater.

PACKAGING

CONTAC-FS-015 15 oz Aerosol Can

PHYSICAL PROPERTIES

Appearance:	Liquid, clear or green
Specific Gravity:	.85 - .95 g/cc
Shear Adhesion:	Expanded polystyrene fails before bond
Spray Tip:	ES6501
Flammability:	Flammable per ASTM E-681-04
Solvent:	Hexane, Acetone
Shelf Life:	15 months
Freezing:	Not damaged by freezing but return to room temp before use.

KEY FEATURES

- Permanent Bonds
- Will not attack polystyrene
- Water Resistant
- Fast Tack
- No Chlorinated Solvents
- No ODS (Ozone Depleting Substances)



See SDS for Proper Handling and Safety Information



605 Wesleyan Dr SW
Atlanta GA 30336

678-904-0038

www.con-dri.com