



Fast Tack * Strong Bonds High Temp Resistance * Low VOCs

CONTACT HD Heavy Duty Adhesive is a high performance versatile industrial strength contact adhesive. Water resistant and temperature resistant to over 200°F, CONTACT HD is designed for bonding a wide range of substrates and construction applications: chamfer, reveal, panel edge forms, wood, veneers, fiberglass and plastic.



PRODUCT USAGE

CONTACT HD Heavy Duty Adhesive is designed to be applied to both surfaces about to be joined. Spray an even coat of adhesive with at least 80% to 100% coverage of each surface. Allow to dry 3-5 minutes until tacky. Place the surfaces together and apply pressure evenly across the full bonding surface. For best results: Make sure that the surfaces are dry and free from dirt, grease, oil or other contaminants. Ensure that the adhesives and substrates are at 60°F or higher. If surfaces are porous, a second coat is recommended after the first has dried and become tacky.

STORAGE

Do not store in direct sunlight or in areas with temperatures of 120°F or greater.

PACKAGING

CONTACT-HD-013 13 oz Aerosol Can

PHYSICAL PROPERTIES

Appearance:	Liquid, clear or red
Specific Gravity:	.95 + .02
Shear Adhesion:	>100psi and >200°F
Spray Tip:	ES4001
Spray Pattern:	Pebble Spray
Flammability:	Flammable per ASTM E-681-04
VOC:	No VOC's, No ODS, No HAPS
Shelf Life:	15 months
Freezing:	Not damaged by freezing but return to room temp before use.

KEY FEATURES

- No VOCs
- SCAQMD Rule 1168 & OTC Compliant
- LEED Compliant
 - LEED Schools EQ Credit 4.0
 - LEED Core & Shell EQ Credit 4.0
 - LEED ND & CI EQ Credit 4.1
 - LEED EB MR Credit 3.0
 - MR Credit 5.1
- Fast Tack Bond Performance
- High Temperature resistance
- Pebble Spray Pattern



See SDS for Proper Handling and Safety Information



605 Wesleyan Dr SW
Atlanta GA 30336

678-904-0038

www.con-dri.com