



**Flammable DOT * NO ODS * Non-Chlorinated Solvent
Superior Bond Performance * Fast Tack * Water Resistant**

CONTAC MU multi-use adhesive - specifically designed for construction applications such as foundation insulation (xps & eps), chamfer / reveal (wood & pvc), plastic sheeting, asphaltic membranes, expansion joint (foam, fiber, cork, sponge rubber), fiberglass, glass, fabrics, foam, cork and particle board



PRODUCT USAGE

For best results, ensure that the adhesives and substrates have been conditioned above 60°F. Make sure that the surfaces are dry and free from dirt, grease, oil or other contaminants. It is always good practice to test specific substrate bonding prior to job. Ensure that the valve on canister is fully open. Position gun 8 to 10 inches away from surface and spray CONTAC MU Multi-Use Adhesive evenly across the surface without puddling. Spray adhesive on both surfaces to be adhered, horizontally for one and vertically for the other. Allow to dry 2 to 4 minutes until tacky and then join surfaces together applying firm pressure evenly across the bond surface. After use, engage the trigger lock on spray gun and store canister in dry area away from direct sunlight.

STORAGE

After use, do not close the valve. Leave the gun and hose connected to the canister. Recommended to store canister off the floor if temperatures below 60°F.

PACKAGING

CONTAC-MU-009 9 lbs Canister
CONTAC-MU-030 30 lbs Canister

PHYSICAL PROPERTIES

Appearance:	Liquid, clear or red
Specific Gravity:	.65 - .75 g/L
Spray Tip:	Q tip
Spray Pattern:	Web Spray
Flammability:	Flammable per ASTM E-681-04
Solvent:	Hydrocarbons
Shelf Life:	15 months
Freezing:	Not damaged by freezing but return to room temp before use.

KEY FEATURES

- No ODS (Ozone depleting substances)
- Non-Chlorinated Solvent
- Superior Bond Performance
- Fast Tack
- Water Resistant



See SDS for Proper Handling and Safety Information



605 Wesleyan Dr SW
Atlanta GA 30336

678-904-0038

www.con-dri.com