



Con-Dri Mastic

Con-Dri Mastic is a commercial grade trowelable waterproofing mastic based on polymer modified asphalt emulsion. Con-Dri Mastic is used as a below-grade exterior waterproofing compound and exhibits excellent strength, adhesion, and flexibility. Con-Dri Mastic is a premium grade waterproofing compound used in commercial building construction for detailed applications.

Con-Dri Mastic can be effectively used as a sealant or patch for tie holes, protrusions, penetrations, cold joints and honeycombs. This product is also a great choice for repairing cracks, seam failures and other water penetration points on existing structures. Con-Dri Mastic is also used as an adhesive for flashing and other termination materials.



Applications

- Masonry Foundations
- Pre-Cast Foundations
- Poured Foundations
- Horizontal

Property	Testing	Value
Color		Black/Brown
Solids		63% $\pm$ 2%
Thickness		40-60 mil dry
Tensile Strength	ASTM D 412	87 psi
Elongation	ASTM D 412	1800%
MVT	ASTM E 96	0.19 gr/hr* sq. ft.
Adhesion to Concrete	ASTM C 834	Exceeds
Shore Hardness Crack	ASTM C 836	75
Bridging	ASTM C 836	Exceeds
Low Temp Flexibility	ASTM C 836	No Cracking
Perm Rating	ASTM C 836	0.38 perms

